

## 日東コン 材質 S (ステアタイト系) 規格表

形式名	端子構造	公称 静電容量 pF±10%	定格電圧		定格 KVA (1MHz)		最大値			寸法 (mm)			備考
			50°C kV <sub>DC</sub>	70°C kV <sub>DC</sub>	50°C	70°C	HF kV	電流 [A]		D ±10%	T ±3	H ±3	
								50°C	70°C				
SD110C-S	S	80	14	11	21	14	4	11	9	110	4.0	29.0	
SD110C-S	S	100	14	11	21	14	4	12	10	110	4.0	29.0	
SD80C-S	S	70	10	8	11	7.5	4	10	8	80	3.0	27.0	
SD80C-S	S	80	10	8	11	7.5	4	10	8	80	2.0	26.0	
SD80C-S	S	100	10	8	11	7.5	4	10	8	80	2.0	26.0	
SD60C-S	S	20	8	7	6	4	4	5	4	60	4.0	25.0	
SD60C-S	S	25	8	7	6	4	4	6	5	60	4.0	24.0	
SD60C-S	S	30	8	7	6	4	4	6	5	60	4.0	22.5	
SD60C-S	S	50	8	7	6	4	4	7	6	60	2.0	22.5	
SD40C-S	S	10	5	4	3	2	4	3.7	3	40	5.0	25.0	
SD40C-S	S	15	5	4	3	2	4	3.7	3	40	4.0	24.0	
SD40C-S	S	20	5	4	3	2	4	3.7	3	40	2.5	22.5	
SD40C-S	S	25	5	4	3	2	4	5.0	4	40	2.5	22.5	
SD30C-S	S	5	3	2.5	2	1.5	2	1.8	1.5	30	4.0	24.0	
SD30C-S	S	10	3	2.5	2	1.5	2	2.4	2	30	3.5	23.5	
SD30C-S	S	15	3	2.5	2	1.5	2	2.4	2	30	3.0	23.0	
SD30C-S	S	20	3	2.5	2	1.5	2	2.4	2	30	2.2	22.2	
SD30C-S	S	25	3	2.5	2	1.5	2	3.7	3	30	1.7	21.5	
SD20C-S	S	5	2	1.5	1.5	1	2	1.2	1	20	2.6	18.6	
SD20C-S	S	10	2	1.5	1.5	1	2	1.8	1.5	20	1.6	17.6	
SD20C-S	S	15	2	1.5	1.5	1	2	1.8	1.5	20	1.1	17.1	
SD20C-S	S	20	2	1.5	1.5	1	2	1.8	1.5	20	0.8	16.8	